# ScissorLoc<sup>™</sup>DC



# FLOATING SYSTEMS

Aacer ScissorLoc DC's criss-cross, solid wood subfloor creates a dimensionally stable system with excellent natural ventilation capabilities.

The option of the PowerVent<sup>TM</sup> Airflow system adds a feature which will detect moisture and start drying the system with mechanical airflow. The ScissorLoc DC exceeds the DIN, EN and MFMA PUR standards.



# ScissorLoc<sup>™</sup> DC



- 1. Precision-milled Aacer Maple
- 2. 1/2" x 6" (12mm x 140mm) **Dimensional Pine**
- 3. 1/2" x 6" (12mm x 140mm) **Dimensional Pine**
- 4. 3/4" (19mm) Performance Foam
- 5. 6mil Polyethylene Vapor Barrier
- 6. Concrete

#### Certified

Green Status and LEED

Contributors













- FSC® Certified Maple MRc7
- FSC® Certified Subfloor Components - MRc7
- EQ 4.2
- Regional Materials MRc5.1 & 5.2

#### Optional Accessory

PowerVent™

Resilience

3/4" (19mm) Performance Foam

\*Other pad options available. Contact your Regional Sales Manager.

#### Slab Depression

ScissorLoc™ DC with 3/4" (19mm) Performance Foam

- 25/32" (20mm) flooring -2 1/2" (64mm)
- 33/32" (26mm) flooring -2 3/4" (70mm)

#### Optional Construction

Contact your Regional Sales Manager for system configurations.

## Subfloor Construction

System Type

**Testing** Laboratory

U.S. Patent #

Warranty

Solid Pine

#### Floating








#5,299,401


Lifetime available

#### WALL BASE




- 3" x 4" (76mm x 101mm) Vent Cove Base
- 1 1/2" (38mm) Min. Expansion Space
- (2) Layers 1/2" x 6" Dimensional Pine
- MFMA Maple Flooring 25/32" x 2 1/4" (20mm x 57mm)
- 3/4" (19mm) Performance Foam
- Vapor Barrier

## **THRESHOLD**



- 1/4" (6mm) Aluminum
- 1 1/2" (38mm) Min. Expansion Space
- (2) Layers 1/2" x 6" Dimensional Pine
- MFMA Maple Flooring 25/32" x 2 1/4" (20mm x
- 3/4" (19mm) Performance Foam
- Vapor Barrier

#### **EQUIPMENT**



- MFMA Maple Flooring 25/32" x 2 1/4" (20mm x 57mm)
- 1 1/2" (38mm) Min. Expansion Space Required at all Insert & Electrical Penetrations
- Solid Blocking at Insert Penetrations
- Vapor Barrier
- 3/4" (19mm) Performance Foam
- Flush Electrical Box or Scorer's Box
- Flexible Conduit





















It is the policy of Aacer Flooring to

right to change, modify or discontinue

systems, specifications and accessories of all products at any time without notice or

