ScissorLoc[™]II FLOATING SYSTEMS



ScissorLoc II is a dimensionally stable system with excellent natural ventilation capabilities due to its criss-cross, solid wood subfloor design. ScissorLoc II can withstand heavier loads because of its ability to adjust to the contour of the floor.

PowerVent[™] Airflow system is a popular accompaniment to the ScissorLoc series. The system can detect moisture and start drying the floor system with mechanical airflow.

www.AACERflooring.com • 877.582.1181

PARTNER IN SPORT

ScissorLoc[™] II

Available ScissorLoc[™] Floor Systems: I, II, III, DC and LP



- 1. Precision-milled Aacer Maple
- 2. 1" x 6" (19mm x 140mm) Dimensional Pine
- 4. 1/4" (6mm) Performance Foam5. 6 mil Polyethylene Vapor Barrier

4

Foam

Vapor Barrier

Threshold

57mm)

Foam Vapor Barrier

3" x 4" (76mm x 101mm)

(2) Layers 1" x 6" (19mm x

140mm) Dimensional Pine

MFMA Maple Flooring

25/32" x 2 1/4" (20mm x

1/4" (6mm) Performance

1/4" (6mm) Aluminum

(2) Layers 1" x 6" (19mm x 140mm) Dimensional Pine

MFMA Maple Flooring

25/32" x 2 1/4" (20mm x

1/4" (6mm) Performance

1 1/2" (38mm) Min.


Expansion Space

Vent Cove Base 1 1/2" (38mm) Min.


Expansion Space

- 6. Concrete
- 3. 1" x 6" (19mm x 140mm) Dimensional Pine


WALL BASE _



THRESHOLD



EQUIPMENT



1. Floor Plate

4

- 2. 1 1/2" (38mm) Min. Expansion Space Required at all Insert & Electrical Penetrations
- 3. Vapor Barrier
- 4. 1/4" (6mm) Performance Foam
- 5. Flush Electrical Box or Scorer's Box
- 6 Elexible Conduit

Certified

Green Status

and LEED Contributors

Optional

Versions Resilience

Optional

Accessory

Depression

Optional

Subfloor

Testing

Construction

Construction

System Type

Laboratory

U.S. Patent #

Warranty

Slab





- FSC[®] Certified Maple MRc7
- FSC[®] Certified Subfloor Components - MRc7
- EQ 4.2
- Regional Materials MRc5.1 & 5.2
- I, II, III, DC, LP
- 1/4" Performance Foam *Other pad options available. Contact your Regional Sales Manager.
- PowerVent™

ScissorLoc™ II

- 25/32" (20mm) flooring -2 1/2" (64mm)
- 33/32" (26mm) flooring -2 3/4" (70mm)

Contact your Regional Sales Manager for system configurations.

Solid Pine

Floating



#5,299,401

Lifetime available

It is the policy of Aacer Flooring to continuously imporve its line of products. Therefore, Aacer Flooring reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.















