

FIXED RESILIENT



AacerChannel®

AacerChannel® enhances performance in gymnasiums, dance floors

and multipurpose facilities.



TriPower® Pad

4 16guage steel anchored to concrete

5 6mil polyethylene vapor barrier

6 Concrete



Anchorage

Steel Channel

Certified







Green Status **LEED Contributors**





FSC Maple - MRc7 FSC SubFloor Components - MRc7

Regional Materals - MRc5.1 & 5.2

Optional Versions

AacerChannel V.L.P

Resilience

TriPower Pads

Slab Depression

3/4" (19 mm) TriPower Pads

25/32" (20 mm) flooring – 2 ½" (64mm) 33/32" (26 mm) flooring – 2 ¾"" (70mm)

1/2" (12mm) VLP Performance Foam

25/32" (20 mm) flooring - 1 1/4" (48mm) 33/32" (26 mm) flooring - 2 1/4" (54mm)

Subfloor Construction

Pre manufactured pannels

System Type

Fixed Resilient

Testing Laboratory






U.S. Patent#


5,647,183

Warranty


Lifetime available



THRESHOLD



EQUIPMENT



(877) 582-1181 AacerFlooring.com

It is the policy of Aacer Flooring to continuously improve its line of products. Therefore, Aacer Flooring reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.