# Anchored PowerSleeper™ SE FIXED RESILIENT SYSTEM

Aacer's Anchored PowerSleeper<sup>™</sup> SE is a system that fully engages the resilient pad inside a steel channel ensuring uniform performance and increased structural stability. It is suitable for new and retrofit sports floor applications and commercial projects.

www.AACERflooring.com • 877.582.1181

A PARTNER IN SPORT

SPORTS FLOORING

an Infinity Wood Floors Company


## Anchored PowerSleeper<sup>™</sup>SE

Anchored PowerSleeper<sup>™</sup> SE is a uniform and stable floor system. It is perfect for new and retro fit projects. This floor system can be shimmed for uneven substrates.




- 1. Precision-milled Aacer Maple
- 2. 15/32" (12mm) Exposure 1, APA **Rated Sheathing**
- 3. Pre-Engineered Steel Encased (SE) Plywood Sleeper


### WALL BASE



THRESHOLD



#### EQUIPMENT



- 4. 1/2" (12mm) TriPower™ Pad 5. Vapor Retarder 6. Steel Concrete Anchor
- 7. PowerVent Airflow Option
  - 3" x 4" (76mm x 101mm) Vent Cove Base 1. 2. 1-1/2" (38mm) Perimeter Expansion Space
  - Steel Encased Plywood Sleeper 3. 1/2" (12mm) TriPower Resilient Pad 4
  - 5 25/32" (20mm) MFMA Maple
  - Flooring Steel Concrete Anchor
  - 15/32" (12mm) Plywood Subfloor 7
  - 8. Vapor Retarder
  - 1/4" (6mm) Aluminum Threshold 1. 2. 1-1/2" (38mm) Perimeter Expansion
  - Space
  - 3. 1/2" (12mm) TriPower Resilient Pad
  - Steel Encased Plywood Sleeper 4
  - 5. Solid Blocking Near Doorway
  - Steel Concrete Anchor 6.
  - 7. 15/32" (12mm) Plywood Subfloor 25/32" (20mm) MFMA Maple Flooring 8.
  - Floor Plate 1.
  - 1 1/2" (38mm) Min. Expansion Space at all Inserts & Electrical Penetrations 2.
  - 3 Concrete Floor Penetration
  - Solid Blocking at Insert 4.

#### Anchorage

Certified



Drill and Pin

Green Status and LEED Contributors

Resilience

Depression

PowerSleeper Systems

System Type

Construction

Subfloor

Optional

Systems

Testing

Laboratory Partners

Protection

Optional

Slab



- FSC<sup>®</sup> Certified Maple MR • FSC<sup>®</sup> Certified Subfloor Components - MR
- Environmental Quality EQ
- Regional Materials MR

1/2" (12mm) TriPower™ **Resilient** Pad \*Other pad options available.

• 25/32" (20mm) Flooring -2 5/8" (67mm)

Anchored PowerSleeper Anchored PowerLoc Anchored PowerLoc LP

**Fixed Resilient** 

Sleeper Plywood

PowerVent<sup>™</sup> Airflow System



It is the policy of Infinity Wood Floors to continuously improve its line of products. Therefore, Infinity Wood Floors reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchase















